

strongSwan - Bug #28

'make install' fails if 'sysconfdir' does not exist.

22.02.2008 14:57 - Martin Willi

Status:	Closed	Start date:	
Priority:	Low	Due date:	
Assignee:	Andreas Steffen	Estimated time:	0.00 hour
Category:	starter	Resolution:	
Target version:	4.2.0		
Affected version:	5.9.2		

Description

Problem: If we specify the destination using the variable DESTDIR and the '\${sysconfdir}' does not exist, installation fails.

```
[...]$ make install DESTDIR=$HOME/tmp/strongswan
...
Making install in starter
maker2: Entering directory @/home/dcorral/Téléchargement/strongswan-2008-02-21/src/starter'
maker3: Entering directory @/home/dcorral/Téléchargement/strongswan-2008-02-21/src/starter'
test -e "/home/dcorral/tmp/strongswan/usr/local/etc/ipsec.conf" || /usr/bin/install -c ipsec.conf
/home/dcorral/tmp/strongswan/usr/local/etc/ipsec.conf
/usr/bin/install: cannot create regular file @/home/dcorral/tmp/strongswan/usr/local/etc/ipsec.conf': No such file or directory
maker3: *** [install-exec-local] Error 1
maker3: Leaving directory @/home/dcorral/Téléchargement/strongswan-2008-02-21/src/starter'
maker2: *** [install-am] Error 2
maker2: Leaving directory @/home/dcorral/Téléchargement/strongswan-2008-02-21/src/starter'
maker1: *** [install-recursive] Error 1
maker1: Leaving directory @/home/dcorral/Téléchargement/strongswan-2008-02-21/src'
make: *** [install-recursive] Error 1
```

Solution: Check if the '\${sysconfdir}' already exists and create it if not. Add the following line to 'src/starter/Makefile.am' in the target 'install-exec-local':

```
test -e "$(DESTDIR)${sysconfdir}" || $(MKDIR_P) "$(DESTDIR)${sysconfdir}"
```

Or apply the attached patch file.

History

#1 - 22.02.2008 15:54 - Martin Willi

- Status changed from New to Closed

- Affected version set to duplicate

Duplicate of [#29](#).

Files

sysconfdir.patch

428 Bytes

22.02.2008

Martin Willi