

## strongSwan - Bug #3182

### Wrong custom logger struct in set\_level function

20.09.2019 11:26 - Michaël Legagneur

<b>Status:</b>	Closed	<b>Start date:</b>	20.09.2019
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Tobias Brunner	<b>Estimated time:</b>	0.00 hour
<b>Category:</b>	libcharon	<b>Resolution:</b>	Fixed
<b>Target version:</b>	5.8.2		
<b>Affected version:</b>	5.8.1		

**Description**

Hello,

We detect one mistake in the set\_level function about the custom logger. The add\_logger is called with sys->logger instead of custom->logger.  
Please find attached the patch fixing this little mistake.

Best regards,

Michaël

#### Associated revisions

##### Revision b0c84c75 - 20.09.2019 14:16 - Tobias Brunner

daemon: Correctly re-register custom loggers in set\_level()

Fixes: 2080c7e1e232 ("charon: Add custom logger to daemon")  
Fixes #3182.

#### History

##### #1 - 20.09.2019 14:28 - Tobias Brunner

- Category set to libcharon
- Status changed from New to Closed
- Assignee set to Tobias Brunner
- Target version set to 5.8.2
- Resolution set to Fixed

Thanks, fixed in master.

#### Files

0001-Use-the-right-custom-logger-in-set_level-function.patch	831 Bytes	20.09.2019	Michaël Legagneur
--	-----------	------------	-------------------