

strongSwan - Bug #591

strongswan 5.1.3 compile failure when --enable-padlock on FreeBSD 9.2

14.05.2014 04:43 - Dewayne Geraghty

Status:	Closed	Start date:	14.05.2014
Priority:	Normal	Due date:	
Assignee:	Tobias Brunner	Estimated time:	0.00 hour
Category:	freebsd		
Target version:	5.5.1		
Affected version:	5.1.3	Resolution:	Fixed
Description			
<p>The include file byteswap.h is not part of the base system.</p> <p>Creating a file containing bswap_32(x) __bswap32(x) enabled a clean compilation.</p> <p>I'd suggest inclusion of something like http://cgkit.haiku-os.org/haiku/plain/src/system/libroot/posix/glibc/string/byteswap.h be added in your application tar file along with the change to strongswan-5.1.3/src/libstrongswan/plugins/padlock/padlock_sha1_hasher.h from #include <byteswap.h> to #include "byteswap.h" to use the more general location.</p> <p>Regards, Dewayne.</p>			

Associated revisions

Revision fe4ed457 - 31.08.2016 10:52 - Tobias Brunner

padlock: Use builtin bswap32() to fix compilation on FreeBSD

Fixes #591.

History

#1 - 31.08.2016 10:53 - Tobias Brunner

- Tracker changed from Issue to Bug
- Category changed from build to freebsd
- Status changed from New to Closed
- Assignee set to Tobias Brunner
- Target version set to 5.5.1
- Resolution set to Fixed

Should be fixed with the associated commit.